

Take Control by Insourcing.

To succeed in today's competitive business environment, you need to produce quality promotional materials while saving as much time and money as possible. Like many companies, you may be outsourcing your graphics with mixed results. If this is the case, then it's time for a change. Start "insourcing" with a Roland VersaCAMM Series printer/cutter, the right choice for your business. With a VersaCAMM, you will enjoy uncompromising 4-color print quality, high speed performance, and automatic printing and contour cutting all in one device. Best of all, you'll be fully equipped to produce the quality labels, posters and other promotional materials your business demands. It's time to take control with the VersaCAMM.



		SP-540i	SP-300i		
Printing technology		Piezoelectric inkjet	Piezoelectric inkjet		
	Width	210 to 1,371 mm (8.3 to 54 in.) 182 to 762 mm (7.2 to 30 in.)			
	Thickness	Maximum 1.0 mm (39 mil) with liner, for printing Maximum 0.4 mm (16 mil) with liner and 0.22 mm (9 mil) without liner, for cutting			
Media	Roll outer diameter	Maximum 180 mm (7 in.) Maximum 180 mm (7 in.)			
	Roll weight	Maximum 30 kg (66 lb.)	Maximum 20 kg (44 lb.)		
	Core diameter	50.8 mm or 76.2 mm (2 in. or 3 in.)	50.8 mm or 76.2 mm (2 in. or 3 in.)		
Printing/cutting width *1		Maximum 1,346 mm (53 in.) Maximum 736 mm (29 in.)			
Ink cartridges	Types	Exclusive Roland ECO-SOL MAX Exclusive Roland ECO-SOL MAX			
	Capacity	220 cc or 440 cc 220 cc or 440 cc			
	Colors	Four colors (cyan, magenta, yellow, and black)	Four colors (cyan, magenta, yellow, and black)		
Printing resolution (dots per inch)		Maximum 1,440 dpi	Maximum 1,440 dpi		
Cutting speed		10 to 300 mm/s 10 to 300 mm/s			
Blade force		30 to 300 gf 30 to 300 gf			
Blade offset		0 to 1.5 mm (0 to 0.059 in)	0 to 1.5 mm (0 to 0.059 in)		
Software resolution (when cutting)		0.025 mm/step 0.025 mm/step			
Distance accuracy (when printing) '2'3		Error of less than 0.3% of distance traveled, or 0.3 mm, whichever is greater			
Distance accuracy (when cutting) '3		Error of less than 0.4% of distance traveled, or 0.3 mm, whichever is greater When distance correction has been performed (when the setting for [CUTTING MENU] - [CALIBRATION] has been made): Error of less than 0.2% of distance traveled, or 0.1 mm, whichever is greater			
Repetition accuracy (when cutting) *3 *4		0.1 mm or less			
Alignment accuracy for	printing and cutting '3 '5	0.5 mm or less	0.5 mm or less		
Alignment accuracy for printing and cutting when reloading media '3'6		Error of less than 0.5% of distance traveled, or 3 mm, whichever is greater			
Media heating system '7		Print heater, setting range for the preset temperature: 30 to 45C (86 to 112F) Dryer, setting range for the preset temperature: 30 to 50C (86 to 122F)			
Connectivity		Ethernet (10BASE-T/100BASE-TX, automatic switching)			
Power-saving function		Automatic sleep feature	Automatic sleep feature		
Power requirements		AC 100 to 120 V 10%, 7.6 A, 50/60 Hz or AC 220 to 240 V 10%, 3.9 A, 50/60 Hz	AC 100 to 120 V 10%, 5.5 A, 50/60 Hz or AC 220 to 240 V 10%, 2.8 A, 50/60 Hz		
Power consumption	During operation	Approx. 1,030 W	Approx. 730 W		
	Sleep mode	Approx. 14 W	Approx. 14 W		
Assumble males level	During operation	64 dB (A) or less	64 dB (A) or less		
Acoustic noise level	During standby	40 dB (A) or less	40 dB (A) or less		
Dimensions With Stand		2,310 (W) x 740 (D) x 1,125 (H) mm [90.9 (W) x 29.1 (D) x 44.3 (H) in.] 1,700 (W) x 740 (D) x 1,125 (H) mm [66.9 (W) x 29.1 (D) x 44.3 (H) in.]			
Weight (with stand)		112 kg (247 lb.)	89 kg (196 lb.)		
Environmental	Power on	Temperature: 15 to 32C (59 to 90F) [20C (68F) or more recommended], Humidity: 35 to 80%RH (non-condensing)			
	Power off	Temperature: 5 to 40C (41 to 104F), humidity: 20 to 80%RH (non-condensing)			
ncluded items		Stand, power cord, blade, blade holder, media clamps, media flanges, replaceme	nt blade for senarating knife, cleaning kit, software RIP, and user's manual, etc.		

- 1 The length of printing or cutting is subject to the limitations of the program. *2 Using Roland specified media, print travel of 1 m, temperature: 25C (77F), humidity: 50%RH *3 Not assured when the print heater or dryer is used.
- *4 Using Roland specified media, loaded on the shaft, [PREFEED] menu item must be set to "ENABLE," with 25 mm or more for both right and left margins and 35 mm or more front margin, excluding expansion or contraction of the media.

 \$P-540i: Media over 610 mm wide and 4,000 mm long. Media 610 mm wide or less and 8,000 mm long. SP-300i: media 3,000 mm long.

 *5 Provided that media length is under 3,000 mm. Temperature: 25C (77F) Excluding possible shift caused by expansion/contraction of the media.

 *6 Using Roland specified media, data size: 1,000 mm in the media-feed direction, 1,346 mm (SP-540i) or 736 mm (SP-300i) in the carriage-movement direction. No lamination. Automatic detection of crop marks at 4 points when media is reloaded. During cutting, [PREFEED] menu item must be set to "ENABLE." Temperature: 25C (77F) Excludes the influence of misalignment, expansion or contraction of the media.

 *7 Warm-up is required after powerup. This may require 5 to 20 minutes, depending on the operating environment. The preset temperature may fail to be reached depending on the ambient temperature and media width.

	Operating system	Windows® 7 Professional/Ultimate (32/64-bit); Windows Vista® Business/Ultimate (32/64-bit edition), or Windows XP Professional Service Pack 2 or later (32/64-bit)
	CPU	Core™ 2 Duo, 2.0 GHz or faster recommended
	RAM	2 GB or more recommended
Video card and monitor		A resolution of 1280 x 1024 or more recommended
	Free hard-disk space	40 GB or more recommended
	Hard-disk file system	NTFS format
	Optical drive	DVD-ROM drive

*Roland VersaWorks® is a 32-bit application, which runs on 64-bit Windows® with WoW64 (Windows 32-bit on Windows 64-bit).

Roland VersaWorks-Compatible Application Software | Adobe® Illustrator® 10, CS, CS2, CS3, CS4, CS5, CS6; CorelDRAW® 11, 12, X3, X4, X5

	Model	Description
	ESL3-4MG	Magenta, 440 cc
	ESL3-4YE	Yellow, 440 cc
	ESL3-4CY	Cyan, 440 cc
	ESL3-4BK	Black, 440 cc
ECO-SOL MAX INK	ESL3-MG	Magenta, 220 cc
	ESL3-YE	Yellow, 220 cc
	ESL3-CY	Cyan, 220 cc
	ESL3-BK	Black, 220 cc
	SL-CL	Cleaning liquid, 1 pc.
Blades	ZEC-U5022	For thick, reflective and fluorescent vinyl, 2pcs.
Diades	ZEC-U5025	For thick, reflective and fluorescent vinyl, 5pcs.
Blade holders	XD-CH3	Blade holder with blade extension abjuster, made of resin
blade floiders	XD-CH2	Blade holder with blade extension abjuster, made of aluminum
	TU2-54	For SP-540i, rolls up to 30 kg (66.1 lb.) Can only be used during printing
Automated	TU2-30	For SP-300i, rolls up to 30 kg (66.1 lb.)*1 Can only be used during printing
take-up system	TUC-2	Controller for TU2-54 and TU2-30 take-up systems
		#4 OD 0001 Idd's!! i-b's t- 00 I (44

*1 SP-300i can load a media roll weighing up to 20 kg (44 lb.)

Roland DG products that feature this environmental label meet the company's criteria for environmental consciousness, a set of standards based on ISO 14021 self-declaration type II. For more information, please visit www.rolanddg.com.



As an ENERGY STAR® partner, Roland DG Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR is a U.S. registered mark.

Automated take-up system For unattended printing, an option

TU2-54 (for SP-540i) TU2-30 (for SP-300i)



Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. Adobe, PostScript, PostScript 3 and the PostScript logo are trademarks of Adobe Systems Incorporated. PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners. Reproduction or use of copyrighted material is governed by local, national, and international laws. Customers are responsible for observing all applicable laws and are liable for any infringement. Roland DG Corp. has licensed the MMP technology from the TPL Group.



AUTHORIZED DEALER:



Printed in Japan. RDG-416091099 13 MAY A-3 G-S

www.rolanddg.com

Imagine.









Save Time and Money

ook at this print quality. It's just like we ordered it from a professional printer. Now we can take care of rush obs, too, while saving money

Bring your Promotional

Activities to Life

display. Use a wide variety of

and heat transfer paper.

media, including adhesive-back

vinyl, banner, paper, film, tarpaulin

At meetings, we can display and review the quality of our graphics. With a VersaCAMM, we can present more ideas

We can print as many or as few items as we need, all while saving valuable time and money. There is no additional cost to die cut our labels and stickers, either!



Design Create Proof Make Produce Print Die cut Deliver

Achieve Professional Quality Results without Any Special Skills

The VersaCAMM Series is highly With the VersaCAMM, you can achieve professional quality results even without any versatile for an endless range of previous experience. Roland Intelligent Pass applications. With just one device, Control® technology automatically delivers the you can produce decals, labels, smooth gradations and flawless solid colors you stickers, posters, POP, vehicle require. Environmentally-friendly ECO-SOL MAX wraps, heat transfers for apparel ink produces vivid colors for durable graphics. decoration and other promotional items of any size, on demand for both indoor and durable outdoor





Enjoy the Versatility of Printing and Digital Die-Cutting — All in One Device

With VersaCAMM, it's easy to create graphics in unique, custom shapes that add value and attract attention. Using Adobe Illustrator, you can easily draw contour cut lines in virtually any shape around your graphics. VersaCAMM will automatically print and cut your designs. Roland DG pioneered Print&Cut technology and today more than 105,000 Roland printer/cutters have been sold worldwide* making Roland the number one brand of Print&Cut inkjet devices.





Improve Communication

Can you make this label darker and give it a more unique shape? It's nice to be able to review and modify designs so quickly and easily!



It's just about ready! The included RIP software is highly intuitive, making changes and corrections easy. Anyone can learn to use it, so why don't you give it a try next time?



Produce Better, More Creative Ideas




Intuitive Roland Operation Software Included

with our printer, but not anymore.

We used to spend a lot of time adjusting color

Every VersaCAMM comes with VersaWorks, our own RIP software for professional print quality. VersaWorks features the Roland Color System to accurately reproduce the spot colors you select from Roland Color charts and swatch books. Variable Data Printing makes it easy to create a series of individualized prints based on one template, with each print featuring its own photos, messages, numbers and names. In addition, VersaWorks estimates the ink usage and print time for each graphic so you can accurately monitor your time and costs. You can also update your software automatically through the Internet.





Roland

/ersaWorks

with Your Office in Mind

Easy to Use and Designed

VersaCAMM is as easy to operate as any other equipment in your office. Its compact footprint is designed to fit comfortably into your office environment. ECO-SOL MAX ink comes in easy-handling sealed cartridges and are virtually odor free. You also get legendary Roland reliability and world-class service and support, including training through Roland workshops and seminars.













